

AN APPLICATION CONTAINER THAT ALLOWS CONCURRENT EXECUTION ON MULTIPLE NODES IN A CLUSTER

Technical Field

The present invention relates to a field of packages utilized on clusters of computer systems. More specifically, the present invention relates to failing-over of applications configured to run on clustered computer systems and a method of eliminating the need to fail-over applications.

Background

Commonly, pluralities of computers, databases, printers and other computing or computing related devices are often established in clusters or as members or elements of a network, hereafter, collectively "Clusters". Cluster are often defined as parallel or distributed systems that consist of a collection of interrelated whole computers, that is utilized as a single, unified computing source. As such, it is commonly appreciated that Clusters commonly consist of computing devices (i.e., Nodes) and other peripheral devices to which access thereto may be controlled by particular Nodes. Clusters enable information system managers to share a computing load over several systems, thereby enhancing the capabilities of the system as a whole, minimizing the adverse effects of failures of certain Nodes or devices on a Cluster, and allowing for the expansion of capacity and capabilities of a given Cluster by adding additional or different Nodes and/or devices to the Cluster. Often Clusters are designed to be Highly Available (i.e., the resources associated with the Cluster have a minimum operating reliability, often measured in the 99.99% range and better). As is well known in the art, High Availability implies that faults in services provided by a Cluster will be detected within a specified time parameter and restored within a specified time parameter.

As Clusters have increased in use, size and complexity, products have been developed that manage such Clusters. One such product is SERVICEGUARD®, developed by HEWLETT PACKARD®. In order to provide the desired High Availability, many of the Cluster management products today utilize a fail-over mechanism when a fault is detected on a Node of a Cluster. The fail-over mechanism basically provides that when a Node on which an application is running fails, for whatever reason, the application is "failed-over" to another Node. In the fail-over process, essentially, the application is restarted on a new Node within a given amount of time. Cluster managers often utilize "Packages", that contain all the resources that an

1 application might need in order to run on a Node. These Package essentially provide the
2 information needed by the fail-over Node in order to restart the application. Examples of
3 information a Package may contain include information relating to the type of storage an
4 application utilizes, the IP addresses that it uses for clients that connect to the application
5 and other information that basically enables the application to run on the system. Cluster
6 management tools, such as SERVICEGUARD®, often are capable of monitoring
7 Packages and starting them as necessary in order to activate an application on a Cluster.
8 Further, when a fail-over occurs, it is the Package that is usually provided to the fail-over
9 Node by the Cluster manager.

10 Further, in addition to providing a container of resources needed to fail-over an
11 application, Packages also provide other benefits. Since all the resources are in one
12 container, a Package makes it easy for Cluster managers to monitor and manage the
13 associated application. Cluster managers, via the Package, can see what components are
14 functioning optimally and also extend the application in interesting ways. For example, if
15 storage devices need to be added for use with a given application, the needed devices can
16 merely be added to the Package and then be available to the application regardless of the
17 Node on which the Package is currently running.

18 However, as Clusters become more common, many new applications are being
19 developed which are essentially, "Cluster Aware", i.e., they appreciate the fact that the
20 application is not merely running on a single computer and instead is running on a Node
21 of a Cluster. With Cluster Aware applications, it is often undesirable to require an
22 application to fail-over to a new Node whenever a fault is detected, because such fail-over
23 is often inefficient, and needed data is often lost. Further, many of these Cluster Aware
24 applications desire to implement instantiations of themselves on every Node in the
25 Cluster. As such, they often do not behave as non-Cluster aware applications when a fail-
26 over occurs because of the instantiations of themselves often are not amenable to the
27 commonly utilized fail-over processes. Examples of Cluster aware applications include
28 volume management services, and ORACLE® database applications, where the database
29 is implemented on multiple Nodes for performance purposes.

30 In particular, ORACLE® database operations are commonly implemented on a
31 Cluster such that each Node has a specific instance of the ORACLE® application. Each
32 Node is capable of implementing the application but does not know that the application
33 also exists on other Nodes of the Cluster. As such, the application is commonly
34 implemented simultaneously on multiple Nodes, thereby wasting and inefficiently

utilizing Cluster resources. Thus, a need exists for a process which enables Cluster aware applications to maintain High Availability without requiring the application to fail-over to other Nodes.

One way to provide for the multiple instantiations of applications on multiple Nodes in a Cluster manager system is to hard-code the multiple instantiations into the source code for the Cluster management software. This hard-coding enables the Cluster management software to appreciate, at start-up, that multiple copies of an application are to be implemented on the Nodes of the Cluster and to automatically start up the multiple instantiations of the applications on the multiple Nodes. While this process works for existing applications (whose needs are known), it is not very adaptable since any new application desiring to be Cluster Aware requires recoding of the source code for the Cluster management software. Thus, there is a need for a process that provides High Availability to Cluster Aware applications while being agnostic as to the particular application being implemented.

Summary

The present invention provides a process for providing High Availability in a Cluster without utilizing a fail-over mechanism. More specifically, the present invention utilizes a Multi-Node Package (MNP) to concurrently run on multiple Nodes on a Cluster and thereby provide the desired operational performance without the downtime associated with fail-over operations.

Instead of initiating a Package on a single Node, the present invention initiates a Package on every Node (or a desired percentage of Nodes) on a Cluster. Instead of an application failing-over to another Node, to ensure High Availability, the MNP merely shifts responsibilities for an application having faults or even possible faults on a first Node to another Node at which another instance of the Package is operating.

Description of the Drawings

The detailed description will refer to the following drawings, wherein like numbers refer to like elements, and wherein:

Figures 1A and 1B are representative flow charts of how a Cluster management system implementing the present invention utilizes the MNP of the present invention to provide High Availability applications.

Detailed Description

As mentioned previously, the present invention provides a process for providing High Availability of applications implemented on a Cluster by utilizing MNPs which do

not need or utilize a fail-over mechanism. The process utilizes any Package well known in the art and does not require specialized Packages or other applications. One example of a Package description is provided below:

```
*****
***
**** HIGH AVAILABILITY PACKAGE CONFIGURATION FILE (template)
****
*****
***
***** Note: This file MUST be edited before it can be used.
*****
*** For complete details about package parameters and how to set them,
*****
*consult the MC/SERVICEGUARD or SERVICEGUARD OPS Edition
manpages**
*** or manuals.
*****
#*****
***
# Enter a name for this package. This name will be used to identify the package
when viewing or manipulating it. It must be different from the other configured
package names.
PACKAGE_NAME          pencil
PACKAGE_TYPE           MULTI_NODE
NODE_NAME              *
RUN_SCRIPT              /etc/cmcluster/pencil/pencil.control
RUN_SCRIPT_TIMEOUT     NO_TIMEOUT
HALT_SCRIPT             /etc/cmcluster/pencil/pencil.control
HALT_SCRIPT_TIMEOUT    NO_TIMEOUT
SERVICE_NAME          samba_nmb_pencil
SERVICE_FAIL_FAST_ENABLED NO
SERVICE_HALT_TIMEOUT  300
SERVICE_NAME          samba_smb_pencil
SERVICE_FAIL_FAST_ENABLED NO
SERVICE_HALT_TIMEOUT  300
SUBNET                 15.13.168.0
AUTO_RUN               YES
LOCAL_LAN_FAILOVER_ALLOWED YES
NODE_FAIL_FAST_ENABLED NO
```

By utilizing commonly available Packages, the present invention provides programmers and system designers with tremendous latitude and adaptability, as specialized code is not needed nor are changes to the source code required in order to expand an application's capabilities or to implement a Cluster aware application on a Cluster.

1 The present invention is configured such that when the Cluster management
2 software detects a new Cluster aware application that is to be implemented on the Cluster,
3 the software obtains the Package associated with one Node of the Cluster, copies the
4 Package and loads the Package onto the desired other Nodes of the Cluster. The Cluster
5 management software knows of the existence of the Package on the other Nodes of the
6 Cluster, such that whenever a fault occurs on one Node, other Nodes may be utilized to
7 immediately implement the application without requiring a fail-over routine copying the
8 needed information contained in the Package.

9 For one embodiment of the present invention, whenever an application is initiated
10 on one Node of the Cluster, it also must have a Package initiated on every other Node of
11 the Cluster. This embodiment is referred to as the System MNP (SMNP) and is
12 commonly utilized when an application utilizes a Cluster membership roster to
13 communicate amongst themselves.

14 However, another embodiment of the present invention does not require every
15 Node to be running an instance of the Package. This configuration is referred to as the
16 General Purpose MNP (GMNP) and might be utilized to balance a load on a Cluster
17 while also providing High Availability. For example, an application might be configured
18 to be run on only 50% of the Nodes, instead of all the Nodes on the Cluster. When a fault
19 occurs on one Node, a second Node (for example, from the 50% containing the Package)
20 suitably continues the operation of the application without requiring a fail-over to occur.

21 Referring now to Figures 1A and 1B, one embodiment of how a system utilizing
22 the MNP of the present invention might be configured to operate in order to provide High
23 Availability to an application running on a Cluster is shown. As shown, this process
24 begins when an application is to be loaded onto a Node of a Cluster (Block 102). At the
25 time of loading, the Package associated with the application is configured into the Cluster
26 by informing the Cluster manager that there is a configuration change. This notification
27 may be accomplished through a command, an input via a Graphical User Interface (GUI),
28 or other methods known in the art. At this time, the Cluster manager performs some
29 verifications of the new Package by confirming that all the attributes specified in the
30 Package configuration are legitimate. One of these attributes will indicate whether the
31 Package is a failover type, a GMNP type, or a SMNP type.

32 If the Package is a failover type (Block 104) the processing ends and the Cluster
33 manager knows that if a failover condition occurs, it will restart the Package on another
34 Node (Block 106). The processing then continues with Block 110, as explained

hereinbelow. If the application is an MNP application (i.e., either a GMNP, and SMNP, or any other type of MNP), the failover behavior will not occur, but instead an instance of the Package will be started on all the Node (in the case of SMNP) or some subset of the Node (in the case of GMNP) (Block 108).

Further, it is to be appreciated that an application may or may not be Cluster Aware and still may utilize an MNP. However, since a Cluster Aware application generally knows that it has peer instances running on other Node in the Cluster, the present invention makes it easier to configure Cluster Aware applications so that how the specific application behaves (during start-up and during the handling of failures by instances of the application) is better controlled by the Cluster manager.

Referring again to Figures 1A and 1B, Block 108, at this instance all Nodes, or those designated Nodes, on the Cluster contain an instantiation of the Package (when the Package is of the MNP type). It is to be appreciated, that for certain applications, the Package may be an extremely large segment of operating instructions, software codes and other information that may be implemented by each Node on the Cluster. As such, the present invention may increase the load requirements for the Cluster as a whole, while eliminating the need to fail-over applications. Thus, those skilled in the art appreciate that, in certain circumstances, the General Purpose MNP embodiment may consider trade-offs between load factor and fail-over success that occur with the implementation of the present invention in deciding upon which Nodes a Package is to instantiated.

Referring again to Figures 1A and 1B, after the Package has been loaded on the desired Nodes of the Cluster, processing then continues with the application itself being implemented on the desired Node, i.e., herein the primary Node (Block 110). The application then continues to process on the primary Node as according to its normal routines and specifications. Meanwhile the Cluster management software preferably continues to monitor the implementation of the application and seeks to detect faults in the application (Block 112).

If a fault in the application is not detected, the application continues processing on the primary Node (Block 114) until either the application is terminated (Block 116) or a fault is detected (Block 112), whichever occurs first.

When a fault is detected, the Cluster management system suitably proceed along one of two paths (Block 113). If the Package is a MNP, the Cluster management takes appropriate actions which may include instructing a second Node (at which an instantiation of the Package was previously loaded) to assume the processing

1 know that an instance of the package has changed state on a particular Node (i.e., started
2 or stopped). Such capabilities may be desired for Cluster aware applications that
3 communicate among their peer instances and may desire to transfer their load from a
4 down instance to an up instance.

5 Further, it is to be appreciated that the process flow shown in Figures 1A and 1B,
6 for purposes of simplicity, combines configuration and instance fault detection into one
7 process flow. Each of which may be considered to be a separate process (i.e., the
8 configuration steps may be considered distinct of the fault detection steps, and vice
9 versa). More specifically, configuration usually occurs without any instances of the
10 applications running. As such, it is not a common thing to make a non-Cluster aware
11 application Clusteraware. The Cluster-aware application is either configured as a set of
12 disjoint traditional failover packages (one package for each Node in the Cluster and these
13 Packages do not specify failover nodes) or it is configured as a MNP.

14 As eluded to earlier, the MNP of the present invention provides certain advantages
15 over the failover type of Package. First, with the MNP, Cluster management is more
16 efficient. If the Cluster manager doesn't provide an MNP, the application is kind of
17 "shoe-horned" into disjointed failover Packages. When these disjointed Packages fail, in
18 order to halt the application on all the Nodes, the Cluster manager has to individually
19 issue a halt command for each Package.

20 Second, Cluster management issues arise when a new node is added to the
21 Cluster. For a SMP in particular, one generally wants to verify that when an existing
22 SMP is configured on the Cluster and the Administrator wants to configure a new Node
23 into the Cluster, that SMP will be able to start an instance of itself on that new node. This
24 verification is built into the "All-Node Package", which might be a SMP that concurrently
25 runs on all up Nodes or it might be a traditional failover package that can failover to any
26 Node in the Cluster.

27 Further, once a Cluster manager decides whether they want a MNP or a traditional
28 failover package and configure the application Package as such, the Cluster manager then
29 knows to take a different action based upon the type of application Package. If it is a
30 traditional failover package it will failover the application to an adoptive Node. If it is a
31 SMP, it notes the failure and, if appropriate, notifies any Cluster-aware Nodes that may
32 have registered for such notifications of the failure. Further, if the Package is a GMNP, it
33 will do the same thing as a SMP, but in a "load balancing" embodiment. When load
34 balancing, the Cluster manager utilizes the specifications for the Package to determine

1 how to transfer the application. For example, such load balancing may indicate that that
2 Package should run one at least “x” number of Nodes or at least “y”% of the Nodes in the
3 Cluster. As such, the cluster manager may try to start another instance of the package on
4 a Node where an instance of that package is not currently running, or, if the load balance
5 thresholds are being met, the Cluster manager may not start another instance of the
6 Package. A starting of another instance of the Package on another Node, however, is not
7 a failover because any running instances on Nodes that did not fail will continue to run
8 while the new instance is started on the new Node.

9 As such, the present invention provides for High Availability on Cluster aware
10 applications, without using a fail-over technique, by utilizing multiple instantiations of
11 Packages on multiple (if not all) Nodes of a Cluster. Such MNPs provide for near
12 seamless transitions of applications across Nodes.

13 Further, it is also to be appreciated that the processes of the present invention may
14 be suitably utilized to also determine system utilization levels, application efficiencies
15 and other information relating to an implementation of an application.

16 Lastly, while the present invention has been described in the context of process
17 flows, Packages, Clusters and networked environments, it is to be appreciated that the
18 present invention is not so limited. Containers of information (whether they be Packages
19 or in other formats) may be utilized in accordance with the present invention for other
20 and/or additional purposes as provided for in the detailed description, drawing figures and
21 claims.